

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
1/15**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1 Product identifier

Product name: Ethylene Oxide

Trade name: Ethylene oxide 3.0

Additional identification

Chemical name: Ethylene oxide

Chemical formula: C₂H₄O

INDEX No. 603-023-00-X

CAS-No. 75-21-8

EC No. 200-849-9

REACH Registration No. 01-2119432402-53

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Using gas alone or in mixtures for the calibration of analysis equipment.
Using gas as feedstock in chemical processes.
Formulation of mixtures with gas in pressure receptacles.
Biocidal uses.

Uses advised against: Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

Oy AGA Ab
Itsehallintokuja 6
FIN-02600 ESPOO Finland

Telephone: +358 10 2421

E-mail: info@fi.aga.com

1.4 Emergency telephone number: Poison Information Center: open 24 hours a day, tel. 09 471 977

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas	Category 1	H220: Extremely flammable gas.
Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.
Chemically unstable gases	Category A	H230: May react explosively even in the absence of air.

Health Hazards

Acute toxicity (Inhalation - gas)	Category 3	H331: Toxic if inhaled.
-----------------------------------	------------	-------------------------

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
2/15

Skin irritation	Category 2	H315: Causes skin irritation.
Serious eye irritation	Category 2	H319: Causes serious eye irritation.
Germ Cell Mutagenicity	Category 1B	H340: May cause genetic defects.
Carcinogenicity	Category 1B	H350: May cause cancer.
Specific Target Organ Toxicity - Single Exposure	Category 3	H335: May cause respiratory irritation.

2.2 Label Elements

Contains: Ethylene oxide



Signal Words: Danger

Hazard Statement(s):

H220: Extremely flammable gas.
H230: May react explosively even in the absence of air.
H280: Contains gas under pressure; may explode if heated.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H335: May cause respiratory irritation.
H340: May cause genetic defects.
H350: May cause cancer.

Precautionary Statements

Prevention:

P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260: Do not breathe gas/vapors.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of water.
P332+P313: If skin irritation occurs: Get medical advice/attention.
P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.
P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381: In case of leakage, eliminate all ignition sources.

Storage:

P403: Store in a well-ventilated place.
P405: Store locked up.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
3/15

Disposal: None.

Supplemental label information

Restricted to professional users.

2.3 Other hazards: Contact with evaporating liquid may cause frostbite or freezing of skin.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	Ethylene oxide
INDEX No.:	603-023-00-X
CAS-No.:	75-21-8
EC No.:	200-849-9
REACH Registration No.:	01-2119432402-53
Purity:	100%
	The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name:	Ethylene oxide 3.0

SECTION 4: First aid measures

General: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Irritating to eyes, respiratory system and skin. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Irritating to eyes, respiratory system and skin. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
4/15

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam.

Unsuitable extinguishing media: Carbon Dioxide.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products. Incomplete combustion may form carbon monoxide

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters: Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.
Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.

6.3 Methods and material for containment and cleaning up: Provide adequate ventilation. Eliminate sources of ignition. Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4 Reference to other sections: Refer to sections 8 and 13.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
5/15

SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling:** Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.
- 7.2 Conditions for safe storage, including any incompatibilities:** All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Keep away from food, drink and animal feeding stuffs. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.
- 7.3 Specific end use(s):** None.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
6/15

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Ethylene oxide	HTP 8H	1 ppm 1,8 mg/m ³	Finland. Workplace Exposure Limits (2009)

DNEL-Values

Critical component	Type	Value	Remarks
Ethylene oxide	Worker - inhalative, short-term - systemic	5 mg/m ³	-
	Worker - inhalative, long-term - systemic	1,6 mg/m ³	-

PNEC-Values

Critical component	Type	Value	Remarks
Ethylene oxide	Aquatic (freshwater)	0,084 mg/l	-
	Aquatic (intermit. releases)	0,84 mg/l	-
	Sediment (marine water)	0,0329 mg/kg	-
	Sewage treatment plant	13 mg/l	-
	Soil	0,0165 mg/kg	-
	Aquatic (marine water)	0,0084 mg/l	-
	Sediment (freshwater)	0,329 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Gas detectors should be used when quantities of flammable gases or vapours may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges. Do not eat, drink or smoke when using the product.

Individual protection measures, such as personal protective equipment

General information:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
7/15

Eye/face protection:	Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
Skin protection	
Hand Protection:	Wear working gloves while handling containers Guideline: EN 388 Protective gloves against mechanical risks. Material: Butyl rubber. Break-through time: > 30 min Glove thickness: 0,7 mm
Body protection:	Wear fire resistant or flame retardant clothing. Keep suitable chemically resistant protective clothing readily available for emergency use. Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing. Guideline: EN 943 Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.
Other:	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection:	Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Material: Filter AX Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking. Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking. Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
8/15

Odor:	sweetish, ethereal
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
pH:	not applicable.
Melting Point:	-111,7 °C Experimental result, Key study
Boiling Point:	10,7 °C (1.013,25 hPa) Experimental result, Key study
Sublimation Point:	not applicable.
Critical Temp. (°C):	196,0 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Flammable gas
Flammability Limit - Upper (%):	99,99 %(V) Experimental result, Key study
Flammability Limit - Lower (%):	2,6 %(V)
Vapor pressure:	1.456 hPa (20 °C) Experimental result, Key study
Vapor density (air=1):	1,5 AIR=1
Relative density:	0,882 (10 °C)
Solubility(ies)	
Solubility in Water:	No data available.
Partition coefficient (n-octanol/water):	-0,30
Autoignition Temperature:	429 °C Experimental result, Key study
Decomposition Temperature:	Liquid not detonable, but the vapor may be readily initiated into explosive decomp.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,283 mPa.s (10 °C)
Explosive properties:	Not applicable.
Oxidizing properties:	not applicable.

9.2 Other information:	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
Molecular weight:	44,06 g/mol (C ₂ H ₄ O)

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants. May polymerise.
10.4 Conditions to avoid:	Avoid moisture in the installation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
9/15

- 10.5 Incompatible Materials:** Air and oxidizers. Moisture. For material compatibility see latest version of ISO-11114.
- 10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral Product

Based on available data, the classification criteria are not met.

Ethylene oxide

LD 50 (Rat): 330 mg/kg Remarks: Experimental result, Key study

Acute toxicity - Dermal Product

Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation Product

Toxic if inhaled.

Ethylene oxide

LC 50 (Rat, 1 h): 2900 ppm

Repeated dose toxicity Ethylene oxide

NOAEL (Mouse(Female, Male), Inhalation, 10 - 11 Weeks): 10 ppm(m) Inhalation Experimental result, Weight of Evidence study
NOAEL (Rat(Female, Male), Inhalation, 2 yr): 10 ppm(m) Inhalation Experimental result, Weight of Evidence study

Skin Corrosion/Irritation Product

Causes skin irritation.

Ethylene oxide

in vivo (Rabbit): Irritating Experimental result, Supporting study

Serious Eye Damage/Eye Irritation Product

Causes serious eye irritation.

Ethylene oxide

in vivo (Rabbit, 48 hrs): IrritatingEU

Respiratory or Skin Sensitization Product

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
10/15

Germ Cell Mutagenicity Product	May cause genetic defects.
Carcinogenicity Product	May cause cancer.
Reproductive toxicity Product	Based on available data, the classification criteria are not met.
Specific Target Organ Toxicity - Single Exposure Product	Causes damage to red blood cells (haemolytic poison). Causes irritation to the respiratory tract May cause respiratory irritation.
Ethylene oxide	Causes damage to red blood cells (haemolytic poison). Causes irritation to the respiratory tract
Specific Target Organ Toxicity - Repeated Exposure Product	Causes damage to red blood cells (haemolytic poison).
Ethylene oxide	Causes damage to red blood cells (haemolytic poison).
Aspiration Hazard Product	Not applicable to gases and gas mixtures..

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity Product	No ecological damage caused by this product.
Acute toxicity - Fish Ethylene oxide	LC 50 (Pimephales promelas, 96 h): 84 mg/l (Static) Remarks: Experimental result, Key study
Acute toxicity - Aquatic Invertebrates Ethylene oxide	LC 50 (Daphnia magna, 48 h): 212 mg/l (Static) Remarks: Experimental result, Key study
Toxicity to microorganisms Ethylene oxide	EC50 (Alga, 72 h): 240 mg/l

12.2 Persistence and Degradability
Product

Not applicable to gases and gas mixtures..

12.3 Bioaccumulative potential
Product

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
11/15

12.4 Mobility in soil

Product

Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5 Results of PBT and vPvB
assessment

Product

Not classified as PBT or vPvB.

12.6 Other adverse effects:

No ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:

Must not be discharged to atmosphere. Consult supplier for specific recommendations.

Disposal methods:

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container:

16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SECTION 14: Transport information

ADR

14.1 UN Number: UN 1040
14.2 UN Proper Shipping Name: ETHYLENE OXIDE
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.3, 2.1
Hazard No. (ADR): 263
Tunnel restriction code: (B/D)
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

RID

14.1 UN Number: UN 1040
14.2 UN Proper Shipping Name: ETHYLENE OXIDE
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.3, 2.1
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
12/15

IMDG

14.1 UN Number: UN 1040
 14.2 UN Proper Shipping Name: ETHYLENE OXIDE
 14.3 Transport Hazard Class(es)
 Class: 2.3
 Label(s): 2.3, 2.1
 EmS No.: F-D, S-U
 14.3 Packing Group: -
 14.5 Environmental hazards: not applicable
 14.6 Special precautions for user: -

IATA

14.1 UN Number: UN 1040
 14.2 Proper Shipping Name: Ethylene oxide
 14.3 Transport Hazard Class(es):
 Class: 2.3
 Label(s): -
 14.4 Packing Group: -
 14.5 Environmental hazards: not applicable
 14.6 Special precautions for user: -
 Other information
 Passenger and cargo aircraft: Forbidden.
 Cargo aircraft only: Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

The packaging shall be visibly, legibly and indelibly marked as follows:
 Restricted to professional users.

Chemical name	CAS-No.	Concentration
Ethylene oxide	75-21-8	100%

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
13/15

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens and mutagens at work.:

Chemical name	CAS-No.	Concentration
Ethylene oxide	75-21-8	100%

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breast feeding.:

Chemical name	CAS-No.	Concentration
Ethylene oxide	75-21-8	100%

Directive 96/61/EC: concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registry (EPER):

Chemical name	CAS-No.	Concentration
Ethylene oxide	75-21-8	100%

Directive 96/82/EC (Seveso III): on the control of major accident hazards involving dangerous substances:

Chemical name	CAS-No.	Concentration
Ethylene oxide	75-21-8	100%

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Ethylene oxide	75-21-8	100%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Directive 94/9/EC on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.
This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: CSA has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
14/15

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

- Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).
- European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
- European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
- European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.
- International Programme on Chemical Safety (<http://www.inchem.org/>)
- ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
- Matheson Gas Data Book, 7th Edition.
- National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
- The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
- The European Chemical Industry Council (CEFIC) ERICards.
- United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
- Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
- Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.

Training information:

Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

- Flam. Gas 1, H220
- Press. Gas Liq. Gas, H280
- Chem. Unst. Gas A, H230
- Acute Tox. 3, H331
- Skin Irrit. 2, H315
- Eye Irrit. 2, H319
- Muta. 1B, H340
- Carc. 1B, H350
- STOT SE 3, H335

SAFETY DATA SHEET

Ethylene Oxide

Issue Date: 16.01.2013
Last revised date: 21.09.2017

Version: 1.0

SDS No.: 000010021703
15/15

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date:

21.09.2017

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.